








GSM & WIRELESS PRODUCTS PRICE LIST

Product Name	Unit Price	Specification/Description
 GSM Surveillance Eye	24,000/- + Taxes	This product use GSM SIM card. Remote control Real-time audio Infrared light Special Camera Send images to mobile Send images to email Multimode alarm Fixed time monitor: Monitor schedule can be set flexibly with multiple time-intervals. Built-in <u>Lithium Rechargeable battery</u>
 GSM IP PTZ Surveillance Eye	30,000/- + Taxes	Auto dial 6 preset numbers in an emergency Listen in remotely over your cell Work with 120 DB external siren SMS/MMS Alert available Arm and disarm remotely via phone call or SMS Get a MMS image of the surveillance area by sending a SMS command to the host 3 external and 1 built-in cameras , totally 4ch video input Support SD memory card with a maximum 4GB capability, can auto record pictures into SD card Built-in back up rechargeable lithium battery Get MMS image from any channel of the 4 cameras by sending SMS order to the host





Product Name	Unit Price	Specification/Description
 <p data-bbox="298 835 548 898">Central Monitoring system</p>	<p data-bbox="634 716 769 747">125,000/-</p> <p data-bbox="691 783 711 808">+</p> <p data-bbox="662 842 740 873">Taxes</p>	<p data-bbox="824 554 1292 585">Operations for Software Centre</p> <p data-bbox="824 588 1268 810">System running Add/Edit administrator Add/Edit communication protocol Edit Host ID and Remote control commands Edit user distribution map Create client(host) Information</p> <p data-bbox="824 812 1195 844">Function of the Software</p> <p data-bbox="824 846 1133 1035">Login Alarm receiving Center Guarding zones Alarm Records Logs Client information</p> <p data-bbox="824 1037 1032 1068">Administrator</p>



Product Name	Unit Price	Specification
 <p data-bbox="272 976 576 1039">Wireless Door/Window Magnetic Contact</p>	<p data-bbox="657 745 738 777">500/-</p> <p data-bbox="690 808 706 840">+</p> <p data-bbox="657 871 738 903">Taxes</p>	<p data-bbox="820 619 1339 1123"> Power Requirements: DC=12V-8.4V(23A DC=12V battery inside) Current Consumption: less than 20uA less than 15mA while transmitting Transmit Frequency:315±0.2Mhz/433±0.2Mhz Transmit Duration: less than 1s Transmit Distance from host: more than 80m(no obstacle) Installation: less than 15mm between part A and part B Coding Type: Fixed Code Dimension(LWH):71X36X15mm Operating Temp:-10~+40 Humidity: less than 90% Shell Color: White </p>
 <p data-bbox="284 1459 560 1554">High-Power Wireless Door/Window Magnetic Contact</p>	<p data-bbox="657 1228 738 1260">650/-</p> <p data-bbox="690 1323 706 1354">+</p> <p data-bbox="657 1386 738 1417">Taxes</p>	<p data-bbox="820 1134 1339 1638"> Power Requirements: DC=12V-8.4V(23A DC=12V battery inside) Current Consumption: less than 20uA; less than 15mA while transmitting Transmit Frequency:315±0.2Mhz/433±0.2Mhz Transmit Duration: less than 1s Transmit Distance from host: more than 300M(no obstacle) Installation: less than 15mm between part A and part B Coding Type: Fixed Code Dimension(LWH): 71X36X15mm Operating Temp: -10~+40 Humidity: less than 90% Shell Color: White </p>




Product Name	Unit Price	Specification/Description
 <p data-bbox="284 898 565 989">Wireless Magnetometer Roller Shutters</p>	<p data-bbox="651 646 751 680">1,000/-</p> <p data-bbox="691 716 711 743">+</p> <p data-bbox="662 779 740 806">Taxes</p>	<p data-bbox="824 554 1344 1031">Power Requirements □DC=12V-8.4V(23A DC=12V battery inside) Current Consumption: less than 20uA; less than 15mA while transmitting Transmit Frequency:315±0.2Mhz/433±0.2Mhz Transmit Duration: less than 1s Transmit Distance from host :more than 80m(no obstacle) Installation: less than 15mm between part A and part B Coding Type: Fixed Code Dimension(LWH):71X36X15mm Operating Temp:-10□~+40□ Humidity: less than 90%</p>
 <p data-bbox="289 1451 555 1507">Wireless PIR sensor without Adapter</p>	<p data-bbox="651 1199 751 1232">1,000/-</p> <p data-bbox="691 1268 711 1295">+</p> <p data-bbox="662 1331 740 1358">Taxes</p>	<p data-bbox="824 1041 1356 1675">Power Requirements:DC9V Power Requirements:7mA~8mA (While sending) Power Requirements:45uA(While monitor) Operating Frequency:315±0.2Mhz/433±0.2Mhz The largest coverage:12*12m Visual Angle:110° Bracket Adjustable Angle:-45° to +45°(Horizontal line) Bracket Adjustable Angle:-15° to +45°(Vertical line) Response Time:6s Coding Type: Fixed Code Dimension(LWH): 110X65X48mm Lifespan of battery: It can be used half year if send 20 times everyday Operating Temp: -10□~+50□ Shell Color: White</p>



Product Name	Unit Price	Specification/Description
 <p data-bbox="289 961 558 1087">Wireless Curtain PIR Sensor with Adapter and rechargeable battery</p>	<p data-bbox="651 716 748 747">1,500/-</p> <p data-bbox="691 814 708 842">+</p> <p data-bbox="659 877 740 909">Taxes</p>	<p data-bbox="824 558 1317 1161"> Power Requirements □DC12V Power Requirements: 7mA~8mA (While sending) Power Requirements:45uA(While monitor) Operating Frequency:315±0.2Mhz/433±0.2Mhz Visual Angle:110° Bracket Adjustable Angle:15°(Horizontal line) Bracket Adjustable Angle:-15° to +45°(Vertical line) Detecting Range: 8m to 12m Coding Type: Fixed Code Dimension(LWH): 110X65X48mm Lifespan of battery: it can use about half year if send 20 times everyday Operating Temp: -10□~+50□ Shell Color : White </p>
 <p data-bbox="272 1430 574 1461">Wireless Shock Sensor</p>	<p data-bbox="651 1297 748 1329">1,000/-</p> <p data-bbox="691 1360 708 1388">+</p> <p data-bbox="659 1423 740 1455">Taxes</p>	<p data-bbox="824 1171 1333 1549"> Power Requirements:12VDC Power Requirements: 8~12mA (While sending) Power Requirements:0.2uA(While monitor) Operating Frequency:315±0.2Mhz/433±0.2Mhz Transmit distance:300m (no obstacle) Coding Type: Fixed Code Dimension(LWH):71X36X15mm Operating Temp:-10□~+50□ Shell Color :White </p>
 <p data-bbox="305 1839 542 1900">Wireless Glass Breaking Detector</p>	<p data-bbox="651 1654 748 1686">1,500/-</p> <p data-bbox="691 1717 708 1745">+</p> <p data-bbox="659 1780 740 1812">Taxes</p>	<p data-bbox="824 1560 1308 1900"> Power Requirements□DC12V Power Requirements: 20mA (While sending) Power Requirements:0.2uA(While monitor) Operating Frequency:315±0.2Mhz/433±0.2Mhz Coding Type: Fixed Code Dimension(LWH): 90X67X25mm Operating Temp: -10□~+50□ Shell Color :White </p>



Product Name	Unit Price	Specification/Description
 <p data-bbox="305 816 545 875">Wireless Siren for indoor use</p>	<p data-bbox="656 648 743 680">2000/-</p> <p data-bbox="691 718 708 743">+</p> <p data-bbox="662 779 737 810">Taxes</p>	<p data-bbox="824 556 1341 646">Power Requirements :12VDC Current Consumption:40mA (High-low sound)</p> <p data-bbox="824 653 1138 684">Transmit Way: wireless</p> <p data-bbox="824 684 1154 716">Humidity: less than 90%</p> <p data-bbox="824 716 1344 779">Intensity of buzzer'volume:110 decibel at 12VDC, 1FT</p> <p data-bbox="824 779 1252 810">Dimension(LWH):85X37X16mm</p> <p data-bbox="824 810 1235 842">Operational Temp:-10~+40</p>